

Package: longurl (via r-universe)

October 5, 2024

Title Expand Short 'URLs'

Version 0.3.3

Description Tools are provided to expand vectors of short URLs into long 'URLs'. No 'API' services are used, which may mean that this operates more slowly than 'API' services do (since they usually cache results of expansions that every user of the service requests). You can setup your own caching layer with the 'memoise' package if you wish to have a speedup during single sessions or add larger dependencies, such as 'Redis', to gain a longer-term performance boost at the expense of added complexity.

Maintainer Bob Rudis <bob@rud.is>

Depends R (>= 3.6.0)

Encoding UTF-8

License MIT + file LICENSE

LazyData true

Suggests tinytest

Imports httr

RoxygenNote 7.1.0

Repository <https://hrbrmstr.r-universe.dev>

RemoteUrl <https://github.com/hrbrmstr/longurl>

RemoteRef HEAD

RemoteSha 5c6dd05249180da216f60fa15620dccc6e159b03

Contents

expand_urls	2
longurl	3
Index	4

`expand_urls`*Expand a vector of (short) URLs using*

Description

Pass in a vector of URLs (ostensibly "short" URLs) and receive a data frame of the original URLs and expanded URLs

Usage

```
expand_urls(  
  urls_to_expand,  
  warn = TRUE,  
  agent = "longurl-r-package",  
  seconds = 5,  
  .progress = FALSE  
)
```

Arguments

<code>urls_to_expand</code>	character vector of URLs
<code>warn</code>	show any warnings (API or otherwise) as messages
<code>agent</code>	user agent to use (some sites switchup content based on user agents). Defaults to "longurl-r-package".
<code>seconds</code>	number of seconds to wait for a response until giving up. Cannot be <1ms.
<code>.progress</code>	kept for legacy functionality but ignored

Value

a tibble/data frame with the original URLs in `'orig_url'`, expanded URLs in `'expanded_url'` and the HTTP `'status_code'` of the expanded URL. Completely invalid URLs result in a `'NA'` value for `'expanded_url'` & `'status_code'`.

Examples

```
test_urls <- c("http://t.co/D4C7aWYIiA",  
              "1.usa.gov/1J6GNoW",  
              "ift.tt/1L2Llfr")  
big_urls <- expand_urls(test_urls)  
head(big_urls)
```

`longurl`*Tools expand vectors of short URLs into long URLs*

Description

Tools are provided to expand vectors of short URLs into long 'URLs'. No 'API' services are used, which may mean that this operates more slowly than 'API' services do (since they usually cache results of expansions that every user of the service requests). You can setup your own caching layer with the 'memoise' package if you wish to have a speedup during single sessions or add larger dependencies, such as 'Redis', to gain a longer-term performance boost at the expense of added complexity.

Author(s)

Bob Rudis (bob@rud.is)

Index

`expand_urls`, 2

`longurl`, 3