

Package: tdigest (via r-universe)

August 18, 2024

Type Package

Title Wicked Fast, Accurate Quantiles Using t-Digests

Version 0.4.2

Date 2024-06-19

Description The t-Digest construction algorithm, by Dunning et al., (2019) <[doi:10.48550/arXiv.1902.04023](https://doi.org/10.48550/arXiv.1902.04023)>, uses a variant of 1-dimensional k-means clustering to produce a very compact data structure that allows accurate estimation of quantiles. This t-Digest data structure can be used to estimate quantiles, compute other rank statistics or even to estimate related measures like trimmed means. The advantage of the t-Digest over previous digests for this purpose is that the t-Digest handles data with full floating point resolution. The accuracy of quantile estimates produced by t-Digests can be orders of magnitude more accurate than those produced by previous digest algorithms. Methods are provided to create and update t-Digests and retrieve quantiles from the accumulated distributions.

URL <https://git.sr.ht/~hrbrmstr/tdigest>

BugReports <https://todo.sr.ht/~hrbrmstr/tdigest>

Copyright file inst/COPYRIGHTS

Encoding UTF-8

License MIT + file LICENSE

Suggests testthat, covr, spelling

Depends R (>= 3.5.0)

Imports magrittr, stats

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Language en-US

Repository <https://hrbrmstr.r-universe.dev>

RemoteUrl <https://github.com/hrbrmstr/tdigest>

RemoteRef HEAD

RemoteSha e52b7460075afd1ba0885ef3b18878d8f8e1b080

Contents

as.list.tdigest	2
td_add	3
td_create	3
td_merge	4
td_quantile_of	4
td_total_count	5
td_value_at	5
tquantile	6
Index	8

as.list.tdigest	<i>Serialize a tdigest object to an R list or unserialize a serialized tdigest list back into a tdigest object</i>
-----------------	--

Description

These functions make it possible to create & populate a tdigest, serialize it out, read it in at a later time and continue populating it enabling compact distribution accumulation & storage for large, "continuous" datasets.

Usage

```
## S3 method for class 'tdigest'
as.list(x, ...)

as_tdigest(x)
```

Arguments

x	a tdigest object or a tdigest_list object
...	unused

Examples

```
set.seed(1492)
x <- sample(0:100, 1000000, replace = TRUE)
td <- tdigest(x, 1000)
as_tdigest(as.list(td))
```

td_add	<i>Add a value to the t-Digest with the specified count</i>
--------	---

Description

Add a value to the t-Digest with the specified count

Usage

```
td_add(td, val, count)
```

Arguments

td	t-Digest object
val	value
count	count

Value

the original, updated tdigest object

Examples

```
td <- td_create(10)
td_add(td, 0, 1)
```

td_create	<i>Allocate a new histogram</i>
-----------	---------------------------------

Description

Allocate a new histogram

Usage

```
td_create(compression = 100)

is_tdigest(td)
```

Arguments

compression	the input compression value; should be ≥ 1.0 ; this will control how aggressively the t-Digest compresses data together. The original t-Digest paper suggests using a value of 100 for a good balance between precision and efficiency. It will land at very small (think like $1e-6$ percentile points) errors at extreme points in the distribution, and compression ratios of around 500 for large data sets (~1 million datapoints). Defaults to 100.
td	t-digest object

Value

a tdigest object

References

[Computing Extremely Accurate Quantiles Using t-Digests](#)

Examples

```
td <- td_create(10)
```

td_merge	<i>Merge one t-Digest into another</i>
----------	--

Description

Merge one t-Digest into another

Usage

```
td_merge(from, into)
```

Arguments

from, into t-Digests

Value

into
a tdigest object

td_quantile_of	<i>Return the quantile of the value</i>
----------------	---

Description

Return the quantile of the value

Usage

```
td_quantile_of(td, val)
```

Arguments

td t-Digest object
val value

Value

the computed quantile (double)

td_total_count	<i>Total items contained in the t-Digest</i>
----------------	--

Description

Total items contained in the t-Digest

Usage

```
td_total_count(td)

## S3 method for class 'tdigest'
length(x)
```

Arguments

td	t-Digest object
x	a tdigest object

Value

double containing the size of the t-Digest

Examples

```
td <- td_create(10)
td_add(td, 0, 1)
td_total_count(td)
length(td)
```

td_value_at	<i>Return the value at the specified quantile</i>
-------------	---

Description

Return the value at the specified quantile

Usage

```
td_value_at(td, q)

## S3 method for class 'tdigest'
x[i, ...]
```

Arguments

td	t-Digest object
q	quantile (range 0:1)
x	a tdigest object
i	quantile (range 0:1)
...	unused

Value

the computed quantile (double)

Examples

```
td <- td_create(10)

td_add(td, 0, 1) %>%
  td_add(10, 1)

td_value_at(td, 0.1)
td_value_at(td, 0.5)
td[0.1]
td[0.5]
```

tquantile

Calculate sample quantiles from a t-Digest

Description

Calculate sample quantiles from a t-Digest

Usage

```
tquantile(td, probs)

## S3 method for class 'tdigest'
quantile(x, probs = seq(0, 1, 0.25), ...)
```

Arguments

td	t-Digest object
probs	numeric vector of probabilities with values in range 0:1
x	numeric vector whose sample quantiles are wanted
...	unused

Value

a numeric vector containing the requested quantile values

References

[Computing Extremely Accurate Quantiles Using t-Digests](#)

Examples

```
set.seed(1492)
x <- sample(0:100, 1000000, replace = TRUE)
td <- tdigest(x, 1000)
tquantile(td, c(0, .01, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 0.99, 1))
quantile(td)
```

Index

[.tdigest (td_value_at), 5
as.list.tdigest, 2
as_tdigest (as.list.tdigest), 2
is_tdigest (td_create), 3
length.tdigest (td_total_count), 5
quantile.tdigest (tquantile), 6
td_add, 3
td_create, 3
td_merge, 4
td_quantile_of, 4
td_total_count, 5
td_value_at, 5
tquantile, 6